



Article Number: 151-01522

Ratchet P-Clamp, 1.38"–2.01" Bundle Dia, 90° Long, .41" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 140/ctn Description:

Base Data		
	Local Order Number	454.04520
	Local Order Number	151-01522
	Туре	RCD90LM10
	Color	Black (BK)
	Features and benefits	<ul> <li>One-piece ratchet closure design allows for easy installation during pre- or final assembly.</li> <li>Four sizes and multiple configurations handle a wide range of diameters and applications, reducing part inventory.</li> <li>Clamp interior is designed to guide and center bundle to reduce pinching.</li> <li>Easy release feature allows for quick adjustments and maintenance.</li> <li>Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.</li> <li>Steel mounting plate tolerates high torque mounting and is treated to resist chemicals and salt spray.</li> </ul>
	Quantity Per	carton
	Product Description	The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. The Ratchet P-Clamp is offered in four sizes and multiple mounting configurations.
	Short Description	Ratchet P-Clamp, 1.38"–2.01" Bundle Dia, 90° Long, .41" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 140/ctn
Product Dimensions		
	Minimum Tensile Strength (Imperial)	100.0lbs
	Minimum Tensile Strength (Metric)	445.0N
	Length L (Imperial)	7.69"
	Length L (Metric)	195.2mm
	Length L2 (Imperial)	4.59"
	Fixation Method	Screw Mounting
	Length L2 (Metric)	116.7mm
	Variant	90° Long
	Width W (Imperial)	1.37"

generated on: 4/29/2017

## 151-01522



Product   Dimensions			
Cable Tie Width Max. (Metric)   13.2mm		Width W (Metric)	34.9mm
Width W2 (Imperial)   1.181"		Cable Tie Width Max. (Imperial)	0.52"
Width W2 (Metric)   30.0mm		Cable Tie Width Max. (Metric)	13.2mm
Bundle Diameter Min. (Imperial)   1.42"		Width W2 (Imperial)	1.181"
Bundle Diameter Min. (Metric) 36.0mm  Bundle Diameter Max. (Imperial) 2.0*  Bundle Diameter Max. (Imperial) 51.0mm  Mounting Hole Diameter D (Imperial) 0.405*  Mounting Hole Diameter D (Metric) M10  Mounting Hole Centers (Imperial) 1.67*  Stud Size (Metric) M10  Material and Specifications  Material Steel (ST)  Material Shortcut ZN  Flammability UL 94 HB  Operating Temperature -40°F to +257°F (-40°C to +125°C)  ROHS Compliant Yes  Stamping Material Steel (ST)  Logistic and Packaging  Package Quantity (Imperial) 140  Package Quantity (Imperial) 140		Width W2 (Metric)	30.0mm
Bundle Diameter Max. (Imperial) Bundle Diameter Max. (Metric)  Bundle Diameter Max. (Metric)  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  Stud Size (Metric)  M10  Material and Specifications  Material Steel (ST)  Material Shortcut  Flammability  Operating Temperature  A0°F to +257°F (-40°C to +125°C)  ROHS Compliant  Stamping Material  Steel (ST)  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Imperial)  140		Bundle Diameter Min. (Imperial)	1.42"
Bundle Diameter Max. (Metric)   51.0mm		Bundle Diameter Min. (Metric)	36.0mm
Mounting Hole Diameter D (Imperial)   0.405"		Bundle Diameter Max. (Imperial)	2.0"
Mounting Hole Diameter D (Metric)   M10		Bundle Diameter Max. (Metric)	51.0mm
Mounting Hole Centers (Imperial)   1.67"		Mounting Hole Diameter D (Imperial)	0.405"
Stud Size (Metric)  Material and Specifications  Material  Material  Material Steel (ST)  Material Shortcut  Flammability  Operating Temperature  A0°F to +257°F (-40°C to +125°C)  ROHS Compliant  Yes  Stamping Material  Steel (ST)  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Imperial)  Package Quantity (Metric)  140		Mounting Hole Diameter D (Metric)	M10
Material and Specifications  Material  Material  Material Shortcut  Flammability  UL 94 HB  Operating Temperature  ROHS Compliant  Stamping Material  Steel (ST)  Ves  Stamping Material  Steel (ST)  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  140		Mounting Hole Centers (Imperial)	1.67"
Material   Steel (ST)		Stud Size (Metric)	M10
Material Shortcut  Flammability  Operating Temperature  ROHS Compliant  Steel (ST)  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  ZN  UL 94 HB  -40°F to +257°F (-40°C to +125°C)  Yes  Steel (ST)  Steel (ST)			
Flammability  Operating Temperature  -40°F to +257°F (-40°C to +125°C)  ROHS Compliant  Yes  Stamping Material  Steel (ST)  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  140		Material	Steel (ST)
Operating Temperature -40°F to +257°F (-40°C to +125°C)  ROHS Compliant Yes  Stamping Material Steel (ST)  Logistic and Packaging  Package Quantity (Imperial) 140  Package Quantity (Metric) 140		Material Shortcut	ZN
ROHS Compliant Yes Stamping Material Steel (ST)  Logistic and Packaging  Package Quantity (Imperial) 140 Package Quantity (Metric) 140		Flammability	UL 94 HB
Stamping Material Steel (ST)  Logistic and Packaging  Package Quantity (Imperial) 140  Package Quantity (Metric) 140		Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Logistic and Packaging  Package Quantity (Imperial) 140  Package Quantity (Metric) 140		ROHS Compliant	Yes
Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  140		Stamping Material	Steel (ST)
Package Quantity (Metric) 140			
		Package Quantity (Imperial)	140
Customs Number(Schedule B) 3926909987		Package Quantity (Metric)	140
,		Customs Number(Schedule B)	3926909987

generated on: 4/29/2017