

Article Number: 596-00474

Description: Solar Label, Reflective, PHOTOVOLTAIC SYSTEM...RAPID SHUTDOWN, 5.5" x 1.75", Red, 50/pkg

**PHOTOVOLTAIC SYSTEM
EQUIPPED WITH
RAPID SHUTDOWN**

Base Data	
Local Order Number	596-00474
Type	PSEWRS
Color	Red (RD)
Features and benefits	<ul style="list-style-type: none"> • Made with UV stable inks and materials for durability and weather resistance • Supplied with aggressive adhesive to ensure long life • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections • Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers
Quantity Per	roll
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	Pre-Printed Solar Label, Reflective, " PHOTOVOLTAIC SYSTEM EQUIPPED WITH RAPID SHUTDOWN", 5.5" X 1.75", Red
Local Order Number 2	Cross Reference = 10 per pack: 596-00677; Spanish version 50 per roll: 596-00823
Short Description	Solar Label, Reflective, PHOTOVOLTAIC SYSTEM...RAPID SHUTDOWN, 5.5" x 1.75", Red, 50/pkg
Product Dimensions	
Length L (Imperial)	1.75"
Length L (Metric)	44.45mm
Width W (Imperial)	5.5"
Width W (Metric)	139.7mm
Height H (Imperial)	1.75"
Height H (Metric)	44.45mm

596-00474



Material and Specifications		
	Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate
	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	ROHS Compliant	Yes
	Certification/Specification	ANSI Standard Z535.4
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060
	Labels per Column	1
	Labels per Row	1